

APOLLO ferrara stainless steel radiator



APOLLO ferrara stainless steel radiator

Brushed stainless steel, flat panelled radiator

Vertical or horizontal, bottom or side entry

Diverter fitted, load bearing wall required

Far more substantial, rigid and robust than other similar products on the market

SIZE		SECTIONS	OUTPUT		STOCK CODE	PRICE	SIZE
HEIGHT	WIDTH		WATT	BTU			WIDTH
1400	300	5	858	2929	F14SS5S	550.00	300
1400	400	7	1201	4098	F14SS7S	650.00	400
1400	500	9	1543	5267	F14SS9S	750.00	500
1800	300	5	1090	3721	F18SS5S	650.00	300
1800	400	7	1526	5206	F18SS7S	750.00	400
1800	500	9	1961	6692	F18SS9S	850.00	500
2000	300	5	1199	4091	F20SS5S	750.00	300
2000	400	7	1679	5729	F20SS7S	850.00	400
2000	500	9	2157	7360	F20SS9S	950.00	500

EN442 outputs DT50C • Correction factor to DT60C = 1.2675 • Brushed finish - available within 3 to 5 working days • All prices subject to VAT



DIMENSIONS - VERTICAL MOUNTED		
Size nominal: Actual width = (No. sections x 60mm) - 10mm		
	BOTTOM ENTRY	SIDE ENTRY
Back wall to front of rad	70mm	70mm
Back wall to pipe centres	55mm	25mm
Distance between tappings	(No. sections x 60mm) - 60mm	(No. sections x 60mm) - 10mm



DIMENSIONS - HORIZONTAL MOUNTED		
Size nominal: Actual height = (No. sections x 60mm) - 10mm		
	BOTTOM ENTRY	SIDE ENTRY
Back wall to front of rad	70mm	70mm
Back wall to pipe centres	25mm	55mm
Distance between tappings	Width of Rad Less 70mm	Width of Rad



LCTRV15A



TFFK